

Single Head InkJet Coding Printers

Smooth, Reliable Coding and Ultra-Long Working Time



**Handheld
6205B & 6205BL**



New Generation!

BENTSAI Handheld Printer BT-HH6205 Series

0.5 inch Print Height	5 wheels Stable Print	95% Printing Materials
16 H Working Time	600 dpi High Resolution	420g Light-weight

Introducing the Bentsai BT-HH6205. Prints on 95% of materials, lasts 16+ hours, and ultra-light at 420g—efficiency and practicality redefined.

Two Power Supply Options Opt for Wired Up or Wireless



Efficient Online Handheld

One printer for dual use. Take in hand for mobile coding and mount on production line for auto coding.

Everything Included to Start Immediately



All-Inclusive Kit

Everything Included to Start Immediately



Product Model	6205 Handheld (12.7mm) , 6205BL Online-Handheld (12.7mm)
Printing Technology	Thermal Inkjet (TIJ)
Ink Throw Distance	2-5mm(Distance between nozzle plate and print object)
Print Height	2.5mm-12.7mm(1-5 lines)
Optional Ink Cartridges	Water based (42ml*1): Black,Cyan,Magenta,Yellow Solvent Based (42ml*1): Black,Cyan,Magenta,Yellow,White, Green
Operation System	FreeRTOS system
System Language	Chinese/English/German/Arabic/Spanish/Russian/Japanese/Korean/Italian/ Portuguese/French/Hindi/Thai/Vietnamese/Persian/Turkish/Chinese Traditional/ Indonesian/Slovenian/Serbo-Croatian/Czech/Bulgarian/Romanian/Polish/Greek/ Hungarian/Ukrainian/Slovak/Burmese (Avaiable languages vary for different regions)
Display	4.3" High Definition Touch Screen
Status Alarm	Green: Ready Blue: Printing Red: Alarm
Print Applications	Text, Numbers, Images, Logos, 2D codes, Barcodes, Dates, Counter, Database etc.
Printabel Material	Water based ink for porous and semi porous substrates: Paper/Corrugated box/ Wooden/Fiberboard/Cotton etc. Solvent based ink for semi porous and non porous substrates: Plastic/Glass/Metal plates/Alu-foils/Cables etc.
2D code Type	Code128, Code39, EAN8, EAN13, UPCA, ITF(2of5), UPCE
Barcode Type	DataMatrix, QR
Font Type	True type fonts, Dotmatrix fonts
Resolution	300/600dpi
Print Speed	30m/min(fastest at 300 dpi)
Grey level	1-5
Max. Print Size	12.7mm*406mm
Max. Pixel Size	200px* 4800px
External Ports	Handheld only: USB, Power adapte Handheld and Inline: USB, Power adapter and Photoelectric sensor
Battery	2pcs 18650 lithium ion battery, 2600mAh each.Removable and Replaceble
Standby Time	≥16 hours (working when screen off)
Power Adapter	IN:AC100-240V, OUT: DC5V 2A(B), OUT: DC9V 2A(BL) IN:AC100-240V,OUT: DC5V 2A(6210B), OUT: DC9V 2A(6210BL)
Working Environment	Equipment Storage Temperature: -20°C-55°C Working Temperature: 5°C-35°C (Best: 15°C-35°C) Humidity:10%-80%
Memory Size	128M
Net Weight	410g
Packaging Weight	1750g(Aluminum case)
Product Dimension	208*113*45mm
Packaging Dimension	275*115*250mm



Contech Supply Co.,Ltd.

☎ 02-170-8051

✉ contech@contechsupply.co.th

🌐 www.contechsupply.co.th



@contechsupply